

Network Working Group

Request for Comments: 2989 P. Calhoun, S. Glass, Sun Microsystems, Inc.

Category: Informational T. Hiller, P. McCann, H. Shiino, P. Walsh, Lucent

G. Zorn, G. Dommety, Cisco Systems, Inc.

C. Perkins, B. Patil, Nokia Telecommunications

D. Mitton, S. Manning, Nortel Networks

M. Beadles, SmartPipes Inc.

X. Chen, Alcatel

S. Sivalingham, Ericsson Wireless Communications

A. Hameed, Fujitsu

M. Munson, GTE Wireless

S. Jacobs, GTE Laboratories

B. Lim, LG Information & Communications, Ltd.

B. Hirschman, Motorola

R. Hsu, Qualcomm, Inc.

H. Koo, Samsung Telecommunications America, Inc.

M. Lipford, Sprint PCS

E. Campbell, 3Com Corporation

Y. Xu, Watercove Networks

S. Baba, Toshiba America Research, Inc.

E. Jaques, Vodaphone Airtouch

November 2000

## Criteria for Evaluating AAA Protocols for Network Access

### Status of this Memo

This memo provides information for the Internet community. It does not specify an Internet standard of any kind. Distribution of this memo is unlimited.

### Copyright Notice

Copyright (C) The Internet Society (2000). All Rights Reserved.

### Abstract

This document represents a summary of Authentication, Authorization, Accounting (AAA) protocol requirements for network access. In creating this document, inputs were taken from documents produced by the Network Access Server Requirements Next Generation (NASREQ), Roaming Operations (ROAMOPS), and MOBILEIP working groups, as well as from TIA 45.6.

This document summarizes the requirements collected from those sources, separating requirements for authentication, authorization and accounting. Details on the requirements are available in the original documents.

## 1. Introduction

This document represents a summary of AAA protocol requirements for network access. In creating this documents, inputs were taken from documents produced by the NASREQ [3], ROAMOPS [2], and MOBILEIP [5] working groups, as well as from TIA 45.6 [4]. This document summarizes the requirements collected from those sources, separating requirements for authentication, authorization and accounting. Details on the requirements are available in the original documents.

### 1.1. Requirements language

In this document, the key words "MAY", "MUST", "MUST NOT", "optional", "recommended", "SHOULD", and "SHOULD NOT", are to be interpreted as described in [1].

Please note that the requirements specified in this document are to be used in evaluating AAA protocol submissions. As such, the requirements language refers to capabilities of these protocols; the protocol documents will specify whether these features are required, recommended, or optional. For example, requiring that a protocol support confidentiality is NOT the same thing as requiring that all protocol traffic be encrypted.

A protocol submission is not compliant if it fails to satisfy one or more of the MUST or MUST NOT requirements for the capabilities that it implements. A protocol submission that satisfies all the MUST, MUST NOT, SHOULD and SHOULD NOT requirements for its capabilities is said to be "unconditionally compliant"; one that satisfies all the MUST and MUST NOT requirements but not all the SHOULD or SHOULD NOT requirements for its protocols is said to be "conditionally compliant."

## 1.2. Terminology

### Accounting

The act of collecting information on resource usage for the purpose of trend analysis, auditing, billing, or cost allocation.

### Administrative Domain

An internet, or a collection of networks, computers, and databases under a common administration. Computer entities operating in a common administration may be assumed to share administratively created security associations.

**Attendant** A node designed to provide the service interface between a client and the local domain.

### Authentication

The act of verifying a claimed identity, in the form of a pre-existing label from a mutually known name space, as the originator of a message (message authentication) or as the end-point of a channel (entity authentication).

### Authorization

The act of determining if a particular right, such as access to some resource, can be granted to the presenter of a particular credential.

**Billing** The act of preparing an invoice.

**Broker** A Broker is an entity that is in a different administrative domain from both the home AAA server and the local ISP, and which provides services, such as facilitating payments between the local ISP and home administrative entities. There are two different types of brokers; proxy and routing.

**Client** A node wishing to obtain service from an attendant within an administrative domain.

### End-to-End

End-to-End is the security model that requires that security information be able to traverse, and be validated even when an AAA message is processed by intermediate nodes such as proxies, brokers, etc.

**Foreign Domain**

An administrative domain, visited by a Mobile IP client, and containing the AAA infrastructure needed to carry out the necessary operations enabling Mobile IP registrations. From the point of view of the foreign agent, the foreign domain is the local domain.

**Home Domain**

An administrative domain, containing the network whose prefix matches that of a mobile node's home address, and containing the AAA infrastructure needed to carry out the necessary operations enabling Mobile IP registrations. From the point of view of the home agent, the home domain is the local domain.

**Hop-by-hop**

Hop-by-hop is the security model that requires that each direct set of peers in a proxy network share a security association, and the security information does not traverse a AAA entity.

**Inter-domain Accounting**

Inter-domain accounting is the collection of information on resource usage of an entity within an administrative domain, for use within another administrative domain. In inter-domain accounting, accounting packets and session records will typically cross administrative boundaries.

**Intra-domain Accounting**

Intra-domain accounting is the collection of information on resource within an administrative domain, for use within that domain. In intra-domain accounting, accounting packets and session records typically do not cross administrative boundaries.

**Local Domain**

An administrative domain containing the AAA infrastructure of immediate interest to a Mobile IP client when it is away from home.

**Proxy**

A AAA proxy is an entity that acts as both a client and a server. When a request is received from a client, the proxy acts as a AAA server. When the same request needs to be forwarded to another AAA entity, the proxy acts as a AAA client.

#### Local Proxy

A Local Proxy is a AAA server that satisfies the definition of a Proxy, and exists within the same administrative domain as the network device (e.g., NAS) that issued the AAA request. Typically, a local proxy will enforce local policies prior to forwarding responses to the network devices, and are generally used to multiplex AAA messages from a large number of network devices.

#### Network Access Identifier

The Network Access Identifier (NAI) is the userID submitted by the client during network access authentication. In roaming, the purpose of the NAI is to identify the user as well as to assist in the routing of the authentication request. The NAI may not necessarily be the same as the user's e-mail address or the user-ID submitted in an application layer authentication.

#### Routing Broker

A Routing Broker is a AAA entity that satisfies the definition of a Broker, but is NOT in the transmission path of AAA messages between the local ISP and the home domain's AAA servers. When a request is received by a Routing Broker, information is returned to the AAA requester that includes the information necessary for it to be able to contact the Home AAA server directly. Certain organizations providing Routing Broker services MAY also act as a Certificate Authority, allowing the Routing Broker to return the certificates necessary for the local ISP and the home AAA servers to communicate securely.

#### Non-Proxy Broker

A Routing Broker is occasionally referred to as a Non-Proxy Broker.

#### Proxy Broker

A Proxy Broker is a AAA entity that satisfies the definition of a Broker, and acts as a Transparent Proxy by acting as the forwarding agent for all AAA messages between the local ISP and the home domain's AAA servers.

#### Real-time Accounting

Real-time accounting involves the processing of information on resource usage within a defined time window. Time constraints are typically imposed in order to limit financial risk.

#### Roaming Capability

Roaming capability can be loosely defined as the ability to use any one of multiple Internet service providers (ISPs), while maintaining a formal, customer-vendor relationship with only one. Examples of cases where roaming capability might be required include ISP "confederations" and ISP-provided corporate network access support.

#### Session record

A session record represents a summary of the resource consumption of a user over the entire session. Accounting gateways creating the session record may do so by processing interim accounting events.

#### Transparent Proxy

A Transparent Proxy is a AAA server that satisfies the definition of a Proxy, but does not enforce any local policies (meaning that it does not add, delete or modify attributes or modify information within messages it forwards).

## 2. Requirements Summary

The AAA protocol evaluation criteria for network access are summarized below. For details on the requirements, please consult the documents referenced in the footnotes.

## 2.1. General requirements

These requirements apply to all aspects of AAA and thus are considered general requirements.

General Reqs.	NASREQ	ROAMOPS	MOBILE IP
Scalability a	M 12	M 3	M 30 39
Fail-over b	M 12		M 31
Mutual auth AAA client/server c	M 16		M 30
Transmission level security d		M 6	S 31 39
Data object Confidentiality e	M 26	M 6	M 40
Data object Integrity f	M 16	M 6	M 31 39
Certificate transport g	M 42		S/M 31,33/46

Reliable AAA transport mechanism h	M 22		M 31 32
Run Over IPv4	M 11	M 1	M 33
Run Over IPv6	M 11	1	S 47
Support Proxy and Routing Brokers i	M 12		M 31 39
Auditability j	S 25		
Dual App and Transport Security not required k		O 6	M 40
Ability to carry service-specific attr. l	M 43		S 31 33

## Key

M = MUST

S = SHOULD

O = MAY

N = MUST NOT

B = SHOULD NOT



## Clarifications

- [a] The AAA protocol must be capable of supporting millions of users and tens of thousands of simultaneous requests. The AAA architecture and protocol MUST be capable of supporting tens of thousands of devices, AAA servers, proxies and brokers.
- [b] In the event of failure to communicate with a given server, the protocol must provide a mechanism to change service to another backup or secondary server.
- [c] This requirement refers to the ability to support mutual authentication between the AAA client and server.
- [d] The AAA protocol requires authentication, integrity protection and confidentiality at the transmission layer. This security model is also referred to as hop-by-hop security, whereas the security is established between two communicating peers. All of the security is removed when the AAA message is processed by a receiving AAA entity.
- [e] The AAA protocol requires confidentiality at the object level, where an object consists of one or more attributes. Object level confidentiality implies that only the target AAA entity for whom the data is ultimately destined may decrypt the data, regardless of the fact that the message may traverse one or more intermediate AAA entities (e.g., proxies, brokers).
- [f] The AAA protocol requires authentication and integrity protection at the object level, which consists of one or more attributes. Object level authentication must be persistent across one or more intermediate AAA entity (e.g., proxy, broker, etc), meaning that any AAA entity in a proxy chain may verify the authentication. This implies that data that is covered by object level security CANNOT be modified by intermediate servers.
- [g] The AAA protocol MUST be capable of transporting certificates. This requirement is intended as an optimization, in lieu of requiring that an out-of-band protocol be used to fetch certificates.
- [h] This requirement refers to resilience against packet loss, including:
  - 1. Hop-by-hop retransmission and fail-over so that reliability does not solely depend on single hop transport retransmission.

2. Control of the retransmission mechanism by the AAA application.
  3. Acknowledgment by the transport that a message was delivered successfully, separate from message semantics or syntax evaluation.
  5. Piggy-backing of acknowledgments in AAA messages.
  6. Timely delivery of AAA responses.
- [i] In the Mobile IP AAA architecture, brokers can be in the forwarding path, in which case they act as transparent proxies (proxy brokers). Alternatively, it is also possible to conceive of brokers operating as certifying authorities outside of the forwarding path (routing brokers).
- [j] An auditable process is one in which it is possible to definitively determine what actions have been performed on AAA packets as they travel from the home AAA server to the network device and back.
- [k] The AAA protocol MUST allow communication to be secured. However, the AAA protocol MUST also allow an underlying security service (e.g., IP Security) to be used. When the latter is used, the former MUST NOT be required.
- [l] The AAA protocol MUST be extensible by third parties (e.g., other IETF Working Groups), in order to define attributes that are specific to the service being defined. This requirement simply means that the AAA protocol MUST allow groups other than the AAA WG to define standard attributes.

## 2.2. Authentication Requirements

Authentication Reqs.	NASREQ	ROAMOPS	MOBILE IP
NAI Support a	M 9	M 2	S/M 32,34,39/ 40
CHAP Support b	M 10	M 3	
EAP Support c	M 10	S 3	
PAP/Clear-Text Support d	M 26	B 3	
Re-authentication on demand e	M 17		S 33
Authorization Only without Authentication f	M 9		

## Key

M = MUST

S = SHOULD

O = MAY

N = MUST NOT

B = SHOULD NOT

## Clarifications

- [a] The AAA protocol MUST allow the use of Network Access Identifiers (NAI) [8] to identify users and/or devices.
- [b] The AAA protocol MUST allow CHAP [20] authentication information to be transported. This is commonly used by Network Access Servers that request authentication of a PPP user.
- [c] The AAA protocol MUST allow for Extensible Authentication Protocol (EAP) [14] payload to be transported. Since some EAP authentication mechanisms require more than one round trip, the AAA protocol must allow for such authentication mechanisms to be used. The actual EAP authentication mechanism negotiated MUST be transparent to the AAA protocol. When EAP is used, authentication typically occurs between the user being authenticated and his/her home AAA server.
- [d] While PAP is deprecated, it is still in widespread use for its original intended purpose, which is support of clear-text passwords. As a result, a AAA protocol will need to be able to securely transport clear-text passwords. This includes providing for confidentiality of clear-text passwords traveling over the wire, as well as protecting against disclosure of clear-text passwords to proxies in the forwarding path.
- [e] The AAA protocol MUST allow for a user to be re-authenticated on-demand. The protocol MUST allow for this event to be triggered by either the user, access device (AAA client), or the home or visited AAA server.
- [f] The AAA protocol MUST NOT require that credentials of the user be provided during authorization. The AAA protocol supports authorization by identification or assertion only.

## 2.3. Authorization Requirements

Authorization Reqs.	NASREQ	ROAMOPS	MOBILE IP
Static and Dynamic IPv4/6 Address Assign. a	M 11	M 5	M 32 36
RADIUS gateway capability b	M 44	M 3	M 45
Reject capability c	M 12	M 4	M 39
Precludes layer 2 tunneling	N 11	N 5	
Re-Authorization on demand d	M 18		S 30 33
Support for Access Rules, Restrictions, Filters e	M 11, 19		
State Reconciliation f	M 20		
Unsolicited Disconnect g	M 18		

## Key

M = MUST

S = SHOULD

O = MAY

N = MUST NOT

B = SHOULD NOT

## Clarifications

- [a] The AAA protocol MUST allow a server to provide a static or dynamic address during the authorization phase of a user and/or device. The address assigned MUST be either of type IPv4 or IPv6. If both the client AND the server are aware of a pre-configured address, then it is considered static. Anything else is dynamic.
- [b] This requirement refers to the ability of a new AAA protocol be sufficiently compatible with the large installed base of attributes for existing approaches (RADIUS), such that a server implementation could speak both protocols, or translate between them.
- [c] This requirement refers to the ability of a proxy broker to deny access without forwarding the access request to the AAA server, or to deny access after receiving an access accept from the AAA server.
- [d] This requirement refers to the ability of the AAA client or server to trigger re-authorization, or to the ability of the server to send updated authorization information to the device, such as "stop service." Authorization can allow for a time period, then additional authorization can be sought to continue. A server can initially authorize a user to connect and receive services, but later decide the user is no longer allowed use of the service, for example after N minutes. Authorizations can have a time limit. Re-authorization does not necessarily imply re-authentication.
- [e] This requirement refers to the ability to of the protocol to describe access operational limitations and authorization restrictions to usage to the NAS which includes (but is not limited to):
  - 1. Session expirations and Idle Timeouts
  - 2. Packet filters
  - 3. Static routes
  - 4. QoS parameters

- [f] This requirement refers to the ability of the NAS to use the AAA server to manage resource allocation state. This capability can assist with, but it is not synonymous with, simultaneous user login control, port usage limitations, or IP address pooling.

The design must provide for recovery from data loss due to a variety of faults, including NAS and AAA server reboots, and NAS/AAA server communication outages, and MUST be independent of the accounting stream. The granularity of the recovery of state information after an outage may be on the order of a fraction of a minute. In order to provide for state recovery, explicit session/resource status and update and disconnect messages will be required.

Because of potential multi-domain issues, only systems that allocate or use a resource should track its state.

- [g] This requirement refers to the ability of the AAA server to request the NAS to disconnect an active session for authorization policy reasons.

## 2.4. Accounting Requirements

Accounting Reqs.	NASREQ	ROAMOPS	MOBILE IP
Real-time accounting a	M 14	M 7	M 31
Mandatory Compact Encoding b		M 7	
Accounting Record Extensibility		M 7	M 33
Batch Accounting c	S 21		
Guaranteed Delivery d	M 22		M 31
Accounting Time Stamps e	M 23		M 40
Dynamic Accounting f	M 48		



#### Key

M = MUST

S = SHOULD

O = MAY

N = MUST NOT

B = SHOULD NOT

#### Clarifications

- [a] This requirement may be loosely defined as reporting synchronously with events. Typically the time window is on the order of seconds, not milliseconds.
- [b] The AAA protocol's Accounting data format MUST NOT be bloated, imposing a large overhead for one or more accounting data elements.
- [c] This requirement refers to the ability to buffer or store multiple accounting records, and send them together at some later time.
- [d] This is an application layer acknowledgment. This is sent when the receiving server is willing to take responsibility for the message data.
- [e] This requirement refers to the ability to reflect the time of occurrence of events such as log-on, logoff, authentication, authorization and interim accounting. It also implies the ability to provide for unambiguous time-stamps.
- [f] This requirement refers to the ability to account for dynamic authentication and authorization. To support this, there can be multiple accounting records for a single session.

#### 2.5. Unique Mobile IP requirements

In addition to the above requirements, Mobile IP also has the following additional requirements:

Encoding of Mobile IP registration messages			M 33
Firewall friendly a			M 35
Allocation of local Home agent			S/M 37/41

## Key

M = MUST

S = SHOULD

O = MAY

N = MUST NOT

B = SHOULD NOT

## Clarifications

- [a] A firewall friendly protocol is one which is designed to accommodate a firewall acting as a proxy. For example, this would permit a Home Agent AAA server situated behind a firewall to be reachable from the Internet for the purposes of providing AAA services to a Mobile IP Foreign Agent.

## Notes

- [1] Section 4.2.1 of [2]
- [2] Section 4.2.2 of [2]. Also see [8].
- [3] Section 4.2.3 of [2]. Also see [14].
- [4] Section 4.2.4 of [2].
- [5] Section 4.2.5 of [2].
- [6] Section 4.2.6 of [2].
- [7] Section 4.3 of [2].
- [8] Section 6 of [3]. Also see [6].
- [9] Section 8.2.2.2 of [3]. Also see [14].
- [10] Section 8.2.2.1 of [3]. Also see [14].
- [11] Section 8.3.2.2 of [3]. Also see [7].
- [12] Section 8.1.1 of [3].
- [13] Section 8.1.4.4 of [3].
- [14] Section 8.4.1.2 of [3].

- [15] Section 8.4.2 of [3].
- [16] Section 8.1.3 of [3].
- [17] Section 8.2.1.2 of [3].
- [18] Section 8.3.1.1 of [3].
- [19] Section 8.3.2.1 of [3]. Also see [7].
- [20] Section 8.3.2.3 of [3]. Also see [6], [7].
- [21] Section 8.4.1.3 of [3].
- [22] Section 8.4.1.1 of [3].
- [23] Section 8.4.1.4 of [3].
- [24] Section 8.4.3.1 of [3].
- [25] Section 8.4.3.2 of [3].
- [26] Section 8.2.3.1 of [3].
- [27] Section 8.3.3.1 of [3].
- [28] Section 8.1.4.1 of [3].
- [29] Refer [15]
- [30] Section 3 of [5]
- [31] Section 3.1 of [5]
- [32] Section 4 of [5]
- [33] Section 5 of [5]
- [34] Section 5.1 of [5]
- [35] Section 5.2 of [5]
- [36] Section 5.3 of [5]
- [37] Section 5.4 of [5]
- [38] Section 5.5 of [5]
- [39] Section 6 of [5]
- [40] Section 5.1 of [4]
- [41] Section 5.2.2 of [4]
- [42] Section 8.2.2.2 of [3]
- [43] Section 8.1.2.3 of [3]
- [44] Section 8.1.2.2 of [3]
- [45] Section 5.4 of [4]
- [46] Section 7 of [4]
- [47] Section 8 of [5]
- [48] Section 8.4.1.5 of [3]

### 3. References

- [1] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, March 1997.
- [2] Aboba, B. and G. Zorn, "Criteria for Evaluating Roaming Protocols", RFC 2477, January 1999.
- [3] Beadles, M. and D. Mitton, "Criteria for Evaluating Network Access Server Protocols", Work in Progress.
- [4] Hiller, T., et al., "Cdma2000 Wireless Data Requirements for AAA", Work in Progress.

- [5] Glass, S., Hiller, T., Jacobs, S. and C. Perkins, "Mobile IP Authentication, Authorization, and Accounting Requirements", RFC 2977, October 2000.
- [6] Mitton, D., Beadles, M., "Network Access Server Requirements Next Generation (NASREQNG) NAS Model", RFC 2881, July 2000.
- [7] Mitton, D., "Network Access Server Requirements: Extended RADIUS Practices", RFC 2882, July 2000.
- [8] Aboba, B. and M. Beadles, "The Network Access Identifier", RFC 2486, January 1999.
- [9] Rigney, C., Willens, S., Rubens, A. and W. Simpson, "Remote Authentication Dial In User Service (RADIUS)", RFC 2865, June 2000.
- [10] Rigney, C., "RADIUS Accounting", RFC 2866, June 2000.
- [11] Simpson, W., Editor, "The Point-to-Point Protocol (PPP)", STD 51, RFC 1661, July 1994.
- [12] Sklower, K., Lloyd, B., McGregor, G., Carr, D. and T. Coradetti, "The PPP Multilink Protocol (MP)", RFC 1990, August 1996.
- [13] Simpson, W., Editor, "PPP LCP Extensions", RFC 1570, January 1994.
- [14] Blunk, L. and J. Vollbrecht, "PPP Extensible Authentication Protocol (EAP)", RFC 2284, March 1998.
- [15] Solomon, J. and S. Glass, "Mobile-IPv4 Configuration Option for PPP IPCP", RFC 2290, Feb 1998
- [16] Calhoun, P. and C. Perkins, "Mobile IP Network Access Identifier Extension for IPv4", RFC 2794, March 2000.
- [17] Perkins, C., "IP Mobility Support", RFC 2002, Oct 1996.
- [18] Johnson, D. and C. Perkins, "Mobility Support in IPv6", Work in Progress.
- [19] Aboba, B. and J. Vollbrecht, "Proxy Chaining and Policy Implementation in Roaming", RFC 2607, June 1999.
- [20] Simpson, W., "PPP Challenge Handshake Authentication Protocol (CHAP)", RFC 1994, August 1996.

#### 4. Security Considerations

This document, being a requirements document, does not have any security concerns. The security requirements on protocols to be evaluated using this document are described in the referenced documents.

#### 5. IANA Considerations

This memo does not create any new number spaces for IANA administration.

#### 6. Acknowledgments

Thanks to the members of the Mobile IP, AAA, and NASREQ working groups who have discussed and commented on these requirements. We would also like to thank the members of the AAA evaluation team, Mike St. Johns, Barney Wolf, Mark Stevens, David Nelson, Dave Mitton, Basavaraj Patil and Stuart Barkley for their thorough review of this document.

#### 7. Authors' Addresses

Bernard Aboba  
Microsoft Corporation  
One Microsoft Way  
Redmond, WA 98052

Phone: +1 425-936-6605  
Fax: +1 425-936-7329  
EMail: bernarda@microsoft.com

Pat R. Calhoun  
Network and Security Research Center, Sun Labs  
Sun Microsystems, Inc.  
15 Network Circle  
Menlo Park, CA 94025

Phone: +1 650-786-7733  
EMail: pcalhoun@eng.sun.com

Steven M. Glass  
Sun Microsystems  
1 Network Drive  
Burlington, MA 01845

Phone: +1 781-442-0504  
Fax: +1 781-442-1677  
EMail: steven.glass@sun.com

Tom Hiller  
Wireless Data Standards & Architectures  
Lucent Technologies  
263 Shuman Drive  
Room 1HP2F-218  
Naperville, IL 60563

Phone: +1 630-976-7673  
EMail: tom.hiller@lucent.com

Peter J. McCann  
Lucent Technologies  
Rm 2Z-305  
263 Shuman Blvd  
Naperville, IL 60566

Phone: +1 630-713 9359  
EMail: mccap@lucent.com

Hajime Shiino  
Lucent Technologies Japan Ltd.  
25 Mori Bldg. 1-4-30 Roppongi,  
Minato-ku Tokyo  
Japan

Phone: +81-3-5561-3695  
EMail: hshiino@lucent.com

Glen Zorn  
Cisco Systems, Inc.  
500 108th Avenue N.E., Suite 500  
Bellevue, WA 98004

Phone: +1 425-468-0955  
EMail: gwz@cisco.com

Gopal Dommetty  
IOS Network Protocols  
Cisco Systems, Inc.  
170 West Tasman Drive  
San Jose, CA 95134-1706

Phone: +1 408-525-1404  
Fax: +1 408-526-4952  
EMail: gdommetty@cisco.com

Charles E. Perkins  
Communications Systems Lab  
Nokia Research Center  
313 Fairchild Drive  
Mountain View, CA

Phone: +1 650-625-2986  
Fax: +1-650-625-2502  
EMail: charliep@iprg.nokia.com

Basavaraj Patil  
Nokia Networks  
6000 Connection Dr.  
Irving, TX 75039

Phone: +1 972-894-6709  
Fax: +1 972-894-5349  
EMail: Basavaraj.Patil@nokia.com

David Mitton  
Nortel Networks  
880 Technology Park Drive  
Billerica, MA 01821

Phone: +1 978-288-4570  
EMail: dmitton@nortelnetworks.com

Serge Manning  
Nortel Networks  
2201 Lakeside Blvd  
Richardson, TX 75082-4399

Phone: +1 972-684-7277  
EMail: smanning@nortelnetworks.com

Mark Anthony Beadles  
SmartPipes, Inc.  
565 Metro Place South  
Suite 300  
Dublin, OH 43017

Phone: +1 614-923-5657  
EMail: mbeadles@smartpipes.com

Pat Walsh  
Lucent Technologies  
263 Shuman Blvd.  
1F-545  
Naperville, IL

Phone: +1 630-713-5063  
EMail: walshp@lucent.com

Xing Chen  
Alcatel USA  
1000 Coit Road  
Plano, TX 75075

Phone: +1 972-519-4142  
Fax: +1 972-519-3300  
EMail: xing.chen@usa.alcatel.com

Sanjeevan Sivalingham  
Ericsson Wireless Communications Inc.,  
Rm Q-356C  
6455 Lusk Blvd  
San Diego, CA 92126

Phone: +1 858-332-5670  
EMail: s.sivalingham@ericsson.com

Alan Hameed  
Fujitsu  
2801 Telecom Parkway  
Richardson, TX 75082

Phone: +1 972-479-2089



Mark Munson  
GTE Wireless  
One GTE Place  
Alpharetta, GA 30004

Phone: +1 678-339-4439  
EMail: mmunson@mobilnet.gte.com

Stuart Jacobs  
Secure Systems Department  
GTE Laboratories  
40 Sylvan Road,  
Waltham, MA 02451-1128

Phone: +1 781-466-3076  
Fax: +1 781-466-2838  
EMail: sjacobs@gte.com

Byung-Keun Lim  
LG Electronics, Ltd.  
533, Hoggie-dong, Dongan-ku, Anyang-shi,  
Kyungki-do, 431-080  
Korea

Phone: +82-31-450-7199  
Fax: +82-31-450-7050  
EMail: bklim@lgic.co.kr

Brent Hirschman  
1501 Shure Dr.  
Arlington Heights, IL 60006

Phone: +1 847-632-1563  
EMail: qa4053@email.mot.com

Raymond T. Hsu  
Qualcomm Inc.  
6455 Lusk Blvd.  
San Diego, CA 92121

Phone: +1 619-651-3623  
EMail: rhsu@qualcomm.com

Haeng S. Koo  
Samsung Telecommunications America, Inc.  
1130 E. Arapaho Road  
Richardson, TX 75081

Phone: +1 972-761-7755  
EMail: hskoo@sta.samsung.com

Mark A. Lipford  
Sprint PCS  
8001 College Blvd.; Suite 210  
Overland Park, KS 66210

Phone: +1 913-664-8335  
EMail: mlipfo01@sprintspectrum.com

Ed Campbell  
3Com Corporation  
1800 W. Central Rd.  
Mount Prospect, IL 60056

Phone: +1 847-342-6769  
EMail: ed\_campbell@3com.com

Name: Yingchun Xu  
WaterCove Networks  
One Century Centre, Suite 550  
1750 E. Golf Road  
Schaumburg, IL

Phone: +1 847-477-9280  
EMail: yxu@watercove.com

Shinichi Baba  
Toshiba America Research, Inc.  
PO Box 136,  
Convent Station, NJ 07961-0136

Phone: +1 973-829-4795  
EMail: sbaba@tari.toshiba.com

Eric Jaques  
Vodafone AirTouch  
2999 Oak Road, MS-750  
Walnut Creek, CA 94596

Phone: +1 925-279-6142  
EMail: ejaques@akamail.com

## 8. Intellectual Property Statement

The IETF takes no position regarding the validity or scope of any intellectual property or other rights that might be claimed to pertain to the implementation or use of the technology described in this document or the extent to which any license under such rights might or might not be available; neither does it represent that it has made any effort to identify any such rights. Information on the IETF's procedures with respect to rights in standards-track and standards-related documentation can be found in BCP-11. Copies of claims of rights made available for publication and any assurances of licenses to be made available, or the result of an attempt made to obtain a general license or permission for the use of such proprietary rights by implementors or users of this specification can be obtained from the IETF Secretariat.

The IETF invites any interested party to bring to its attention any copyrights, patents or patent applications, or other proprietary rights which may cover technology that may be required to practice this standard. Please address the information to the IETF Executive Director.

## 9. Full Copyright Statement

Copyright (C) The Internet Society (2000). All Rights Reserved.

This document and translations of it may be copied and furnished to others, and derivative works that comment on or otherwise explain it or assist in its implementation may be prepared, copied, published and distributed, in whole or in part, without restriction of any kind, provided that the above copyright notice and this paragraph are included on all such copies and derivative works. However, this document itself may not be modified in any way, such as by removing the copyright notice or references to the Internet Society or other Internet organizations, except as needed for the purpose of developing Internet standards in which case the procedures for copyrights defined in the Internet Standards process must be followed, or as required to translate it into languages other than English.

The limited permissions granted above are perpetual and will not be revoked by the Internet Society or its successors or assigns.

This document and the information contained herein is provided on an "AS IS" basis and THE INTERNET SOCIETY AND THE INTERNET ENGINEERING TASK FORCE DISCLAIMS ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTY THAT THE USE OF THE INFORMATION HEREIN WILL NOT INFRINGE ANY RIGHTS OR ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

## Acknowledgement

Funding for the RFC Editor function is currently provided by the Internet Society.

